

DALI COUPLER PB G2

DALI COUPLER PB G2 | Light management systems



Areas of application

- Suitable for installation in flush-type boxes
- Individual offices
- Classrooms
- Conference rooms
- Production and assembly facilities

Product family benefits

- Standard pushbuttons/switches can be used
- DALI-2 certified
- DALI Bus powered (No mains connection necessary)
- Multiple couplers connectable to the same DALI line

Product family features

- DALI pushbutton coupler
- 4 floating inputs


Product datasheet

Technical data

Electrical data

Required DALI current (typical)	5 mA
Peak DALI current	12 mA
Maximum start-up time (DALI)	600 ms

Dimensions & weight



Product weight	25.00 g
Length	43.0 mm
Width	43.0 mm
Height	21.0 mm

Temperatures & operating conditions

Ambient temperature range	-20...+50 °C
---------------------------	--------------

Capabilities

Dimming interface	DALI-2
Dimmable	No
Type of installation	Integrated in flush device box
Control interface	DALI

Certificates & standards

Type of protection	IP20
--------------------	------

Logistical data

Commodity code	853710989900
----------------	--------------

Download Data

Product datasheet

File



User instruction
DALI COUPLER PUSHB G2

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4062172087575	DALI COUPLER PB G2	Shipping carton box 60	344 mm x 254 mm x 278 mm	24.29 dm ³	3187.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.