

OT FIT 50/220...240/1A0 CS

OPTOTRONIC FIT CS G1 | Constant Current Compact – Non dimmable



Areas of application

- Emergency lighting systems acc. to IEC 61347-2-13, app. J (CS version only)
- Luminaires with flexible current setting (Tri-Tap for CS version only)
- Luminaires with flexible current setting (LEDset for LT2 S version only)
- Suitable for use in emergency lighting systems, DC capable (CS version only)
- Suitable for indoor SELV installations
- Suitable for luminaires of protection classes I and II
- Suitable for downlights, spotlights and LED panels
- Independent mounting via Cable Clamp Kit possible (depending on version of product)

Product family benefits

- Versatile scope of application due to output power range of up to 54 W
- Fulfill safety requirement due to overload, overtemperature, Hot Plug protection
- High efficiency
- Higher quality of light thanks to low output ripple current

Product family features

- Supply voltage: 220...240 V
- Line frequency: 0 Hz | 50 Hz | 60 Hz
- Line voltage: 198...264 V
- Safety according to EN 61347-1, 61347-2-3, 61347-2-13, 62384
- RI suppression according to EN 55015:2007+A1:2007/CDN
- Line harmonics according to EN 61000-3-2
- Immunity according to EN 61547
- Lifetime: up to 100,000 h (temperature at $T_c = 65^\circ\text{C}$, max. 10 % failure rate)
- LED protection by Hot Plug
- Independent connection via through-looping (CS version only)

Technical data

Electrical data

Nominal input voltage	200...240 V
Mains frequency	50...60 Hz
Input voltage AC	198...264 V ¹⁾
Input voltage DC	176...276 V
Total harmonic distortion	< 10 %
Power factor λ	0.95 ²⁾
ECG efficiency	89 % ³⁾
Device power loss	5.3 W ⁴⁾
Inrush current	24 A ⁵⁾
Max. ECG no. on circuit breaker 10 A (B)	18
Max. ECG no. on circuit breaker 16 A (B)	28
Max. ECG no. on circuit breaker 25 A (B)	-
Surge capability (L/N-Ground)	2 kV
Surge capability (L-N)	1 kV
Nominal output voltage	27...54 V ⁶⁾
U-OUT (working voltage)	60 V
Nominal output current	800 / 900 / 1050 mA ⁷⁾
Output current tolerance	±10 %
Output ripple current (100 Hz)	6 %
Nominal output power	56 W ⁸⁾
Galvanic isolation	SELV

¹⁾ Permitted voltage range

²⁾ Full load at 230 V

³⁾ At full load and 230 V

⁴⁾ Maximum


⁵⁾ $t_{width} = 174 \mu s$ (measured at 50 % I_{peak})

⁶⁾ Maximum 60 V

⁷⁾ ±10%

⁸⁾ Partial load 15...56 W

Dimensions & weight



Mounting hole spacing, length	94.0 mm
Mounting hole spacing, width	58.0 mm
Product weight	170.00 g
Cable cross-section, input side	0.2...1.5 mm ² ¹⁾
Cable cross-section, output side	0.2...1.5 mm ² ¹⁾
Wire preparation length, input side	8.5...9.5 mm
Wire preparation length, output side	8.5...9.5 mm
Length	103.0 mm
Width	67.0 mm
Height	29.5 mm

¹⁾ Solid or flexible leads

Colors & materials

Casing material	Plastic
------------------------	---------

Temperatures & operating conditions

Ambient temperature range	-25...+50 °C
Maximum temperature at tc test point	75 °C ¹⁾
Max.housing temperature in case of fault	110 °C
Permitted rel. humidity during operation	5...85 %

¹⁾ Maximum at the T_c-point

Lifespan

ECG lifetime	50000 h ¹⁾
---------------------	-----------------------

¹⁾ At T_{case} = 75 °C at T_c point / 10% failure rate

Additional product data

Encapsulated	No
---------------------	----

Product datasheet

Capabilities

Dimmable	No
Overheating protection	Automatic reversible
Overload protection	Automatic reversible
Short-circuit protection	Automatic reversible ¹⁾
No-load proof	Yes
Max. cable length to lamp/LED module	2.0 m
Suitable for fixtures with prot. class	I / II
Suitable for emergency lighting	Yes
Type of connection, output side	Push terminal

¹⁾ A short circuit current of max. 1 A may occur. Make sure the load is designed to withstand the short circuit current as well






Certificates & standards

Approval marks – approval	CE / EL
Standards	Acc. to EN 61347-1/Acc. to EN 61347-2-13/Acc. to EN 55015/Acc. to EN 61547/Acc. to EN 61000-3-2/Acc. to EN 62384
Protection class	II
Type of protection	IP20

Logistical data

Temperature range at storage	-20...70 °C
Commodity code	850440829000

Download Data

File	
	Certificates VDE ENEC Certificate 40038447
	Declarations of conformity 489246_DoC_OT FIT CS
	CAD data 685804_OT FIT Housing 3D drawings CAD Data_ISG
	CAD data 685806_OT FIT Housing 3D drawings CAD Data_STEP
	CAD data PDF 685805_OT FIT Housing 3D drawings CAD Data_PDF

Logistical Data

Product datasheet

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899166318	OT FIT 50/220...240/1A0 CS	Shipping carton box 20	357 mm x 222 mm x 96 mm	7.61 dm ³	3622.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.